



KOYO 53248 thrust ball bearings

Bearing No. 53248

| | |
|-------------------------------|-----------------|
| Size | 240x340x81.6 mm |
| Bore Diameter | 240 mm |
| Outer Diameter | 340 mm |
| Width | 81,6 mm |
| d | 240 mm |
| D | 340 mm |
| T1 | 81,6 mm |
| d1 | 335 mm |
| r min. | 2,1 mm |
| A | 122 mm |
| D1 | 244 mm |
| R | 250 mm |
| da min. | 299 mm |
| Da max. | 281 mm |
| ra max. | 2 mm |
| Weight | 20,9 Kg |
| Basic dynamic load rating (C) | 442 kN |
| Basic static load rating (C0) | 1800 kN |
| (Grease) Lubrication Speed | 520 r/min |
| Bearing No. | 53248 |
| T | 81.6 |
| r(min) | 2.1 |
| Ca | 553 |
| Coa | 1800 |
| Cu | 47.8 |
| Grease lub. | 520 |

53248 Bearing 2D drawings and 3D CAD models



Timken MANUFACTURING (THAILAND)CO.,LTD.

| | |
|------------------|------|
| Oil lub. | 800 |
| d1(max) | 335 |
| D1(min) | 244 |
| D2(min) | - |
| D3(min) | - |
| C | - |
| da(min) | 299 |
| Da(max) | 281 |
| ra(max) | 2 |
| (Refer.)Mass(kg) | 20.9 |