



Timken MANUFACTURING (THAILAND)CO.,LTD.



75 mm x 115 mm x 20 mm NSK 6015DDU deep groove ball bearings

Bearing No. 6015DDU

6015DDU Bearing 2D drawings and 3D CAD models

Size	75x115x20 mm
Bore Diameter	75 mm
Outer Diameter	115 mm
Width	20 mm
d	75 mm
D	115 mm
B	20 mm
C	20 mm
r min.	1,1 mm
da min.	81,5 mm
da max	85,5 mm
Da max.	108,5 mm
ra max.	1 mm
Weight	0,649 Kg
Basic dynamic load rating (C)	39,5 kN
Basic static load rating (C0)	33,5 kN
(Grease) Lubrication Speed	3 400 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.645
EAN	0029176063343
Product Group	B00308
Enclosure	2 Seals



Timken MANUFACTURING (THAILAND)CO.,LTD.

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Other Features	Deep Groove Rubber Seal
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6015DDU
Weight / LBS	1.431
Outside Diameter	4.528 Inch 115 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
Bore	2.953 Inch 75 Millimeter
Inner Race Width	0 Inch 0 Millimeter
SRI	6.16
hidYobi	6015DDU



Timken MANUFACTURING (THAILAND)CO.,LTD.

LangID	1
D_	115
SREX	0.025
B_	20
da min	81.5
hidTable	ecat_NSRDGB
SRE	6.16
mass	0.649
GRS rpm	3400
ra	1
SRIX	0.025
D_a	108.5
SRIN	-0.025
C0	33.5
fo	15.8
SREN	-0.025
DE_	106.906
Prod_Type3	DGBB_SR_DD
DA_	11.906
bomp	0
Z_	15
yobi	6015DDU
C_conv	39500
ALPHA_	0
SDM_	95
r	1.1
KBRG	6161
SBRG	10
DI_	83.094