



**130 mm x 230 mm x 40 mm SKF 30226J2 tapered roller bearings**

Bearing No. 30226J2

30226J2 Bearing 2D drawings and 3D CAD models

|                |                  |
|----------------|------------------|
| Size           | 130x230x43.75 mm |
| Bore Diameter  | 130 mm           |
| Outer Diameter | 230 mm           |
| Width          | 43,75 mm         |
| d              | 130 mm           |
| D              | 230 mm           |
| T              | 43,75 mm         |
| B              | 40 mm            |
| C              | 34 mm            |
| a              | 45 mm            |
| d1             | 173 mm           |
| r1 min.        | 4 mm             |
| r2 min.        | 4 mm             |
| r3 min.        | 3 mm             |
| r4 min.        | 3 mm             |
| Ca min.        | 7 mm             |
| Cb min.        | 9,5 mm           |
| da max         | 152 mm           |
| Da min         | 203 mm           |
| Da max.        | 216 mm           |
| db min         | 144 mm           |
| Db min.        | 217 mm           |
| ra max.        | 4 mm             |
| rb max.        | 3 mm             |
| Weight         | 6,85 Kg          |
|                |                  |



## Timken MANUFACTURING (THAILAND)CO.,LTD.

|                               |            |
|-------------------------------|------------|
| Basic dynamic load rating (C) | 369 kN     |
| Basic static load rating (C0) | 490 kN     |
| Fatigue load limit (Pu)       | 51         |
| Reference speed               | 2000 r/min |
| Limiting speed                | 2800 r/min |
| Calculation factor (e)        | 0,43       |
| Calculation factor (Y)        | 1,4        |