



**SKF 23052-2CS5K/VT143 + OH 3052 HE tapered roller bearings**

Bearing No. 23052-2CS5K/VT143 + OH 3052 HE

23052-2CS5K/VT143 + OH 3052 HE Bearing 2D drawings and 3D CAD models

Size	400x240x104 mm
Bore Diameter	400 mm
Outer Diameter	240 mm
Width	104 mm
$d_1$	240 mm
D	400 mm
B	104 mm
$d_2$	289 mm
$d_3$	310 mm
$D_1$	369 mm
$B_1$	145 mm
$B_2$	34 mm
$B_5$	46 mm
b	16.7 mm
K	9 mm
$r_{1,2} - \text{min.}$	4 mm
$d_a - \text{max.}$	289 mm
$d_b - \text{min.}$	272 mm
$D_a - \text{max.}$	385 mm
$B_a - \text{min.}$	11 mm
$r_a - \text{max.}$	3 mm
Basic dynamic load rating - C	1677 kN
Basic static load rating - $C_0$	2550 kN



## Timken MANUFACTURING (THAILAND)CO.,LTD.

Fatigue load limit - $P_u$	212 kN
Limiting speed	360 r/min
Calculation factor - e	0.22
Calculation factor - $Y_1$	3
Calculation factor - $Y_2$	4.6
$d_1$	240 mm
$d_2$	289 mm
$d_3$	310 mm
$D_1$	369 mm
$B_1$	145 mm
$B_2$	34 mm
$B_5$	46 mm
$r_{1,2}$ min.	4 mm
$d_a$ max.	289 mm
$d_b$ min.	272 mm
$D_a$ max.	385 mm
$B_a$ min.	11 mm
$r_a$ max.	3 mm
Basic dynamic load rating C	1677 kN
Basic static load rating $C_0$	2550 kN
Fatigue load limit $P_u$	212 kN
Calculation factor e	0.22
Calculation factor $Y_1$	3
Calculation factor $Y_2$	4.6
Calculation factor $Y_0$	2.8
Mass bearing + sleeve	57.9 kg